



FULL SILO TOTAL ACCESS

Laidig Planetaire reclaimers offer superior performance and dependability for applications with high-density or abrasive materials. Laidig's Planetaire system is engineered to provide completely automated, neartotal clean out, encouraging first-in-first-out (FIFO) material distribution for processing to strict quality-control standards.

The Planetaire provides an access beam which spans the entire diameter of the storage vessel. This

beam offers complete access to all components of the Planetaire, even under a full head-height of material. Serviceable components would include motors, gearboxes, reducers, and the auger cutter blades. Even the entire auger can be removed from a full silo through one of the auger access doors at the end of the beam.

Since the access beam bears the material load and shields the auger from high compressive forces during both the fill and subsequent operation, the Planetaire is usually the system of choice for high-density materials. Coal, dense powders, and heavy or coarse granular materials are ideal applications for the Planetaire.

ABRASION RESISTANCE

Consistent exposure to rugged and abrasive materials can lead to premature wear and the reduction in the life expectancy of critical equipment components.

Laidig has done extensive research and development to provide the very best abrasion resistance options specifically to ensure your equipment will hold up even in the harshest of conditions. These Laidig options include: hardened flight, carburized auger knives and blades, and a total hard-facing of the auger flighting and tube.



Laidig's Planetaire reclaim system is designed for durability and longevity. Hydraulic advance components are utilized to provide ultimate control sensitivity of the Planetaire, increasing running efficiencies and reducing wear on the auger and drive components. All conveying surfaces have been optimized to accommodate highly-abrasive materials, greatly reducing wear. The tapered auger design, together with the load bearing access beam make the Planetaire ideal for dense, heavy materials.



LAIDIG SMART CONTROLS & LAIDIG MACHINE INTERFACE

U_L

The Laidig Planetaire offers intelligent, fully-automated, push-button operation utilizing Laidig's LMI™ (Laidig Machine Interface). The LMI provides the operator with maximum control and flexibility while ensuring the reclaimer is running in a safe and efficient manner. It allows full control and monitoring of the reclaimer's status and operation in a graphic-rich display. The LMI provides an interface to safely control the Planetaire reclaim system, which can be integrated with various types of customer control systems. It can also include remote access capability for monitoring or troubleshooting the system off-site.



*All Laidig LMIs are custom engineered to each reclaim system. UL has tested representative samples and determined they meet the specific, defined requirements based on UL's published and nationally recognized standards for safety.



PERSONNEL ACCESS

Reclaim drive components can be accessed and replaced via the beam, even if in a full silo.

TROLLEY SYSTEM

The trolley assists the installation or removal of motors, reducers and gearboxes from inside the beam.

ACCESS BEAM

The access beam shields reclaim components in dense materials, allowing them to operate smoothly and efficiently. In addition, the beam enables the entry for inspection of all equipment.

AUGER INSPECTION

Access openings in the beam floor allow the reclaim auger and the hardened cutter blades to be inspected and replaced without emptying the silo.

AUGER REMOVAL

The auger may be removed through the access door without emptying the silo.

TAPERED AUGER

A state-of-the-art fully-tapered auger with continuously variable-pitch flighting is designed to require the lowest-possible starting torque and advance pressure. The auger is fit with hardened, replaceable cutters, bolted to abrasion-resistant flighting and auger tube.

DEFLECTOR SHIELD

The center deflector is designed to prevent free-flow, allowing the delivery rate to be controlled entirely by auger rotation. In many cases this eliminates the need for an additional metering device.

DRIVE SYSTEM

The drive system is fully hydraulic with drive components fully accessible and protected from material contamination.



HEAVY-DUTY STORAGE AND RECLAIM SOLUTIONS FOR TOTAL ACCESS EVEN IN A FULL SILO!





Laidig's Planetaire reclaim systems are designed specifically for heavy-duty, industrial applications requiring reclamation of high-density, abrasive materials with poor flow characteristics or other properties which make them difficult to handle. Laidig's turnkey installations typically include concrete silos or monolithic domes.

Laidig Planetaire Specifications

Specifications*	Model PL433 All Hydraulic	Model PL443	Model PL833 All Hydraulic
Storage Diameter Auger Cutting Diameter Auger Capacity Auger Rotation Discharge Opening Reclaim Torque Reclaim Drive HP Hydraulic Power Unit	45' (14 m) 18" (45.7 cm) 100 cfm (2.8 m²/min) 50 RPM 9.33 ft² (0.86 m²) 1x (Base) - 50 HP	45' (14 m) 18" (45.7 cm) 100 cfm (2.8 m²/min) 50 RPM 9.33 ft² (0.86 m²) 1x (Base) 40 HP 1.5HP	80' (24 m) 26" (66 cm) 200 cfm (5.6 m³/min) 35 RPM 9.33 ft² (0.86 m²) 4.2x - 100 HP

^{*} Data shown conveys generalized specifications of the referenced Laidig reclaimers. Material characteristics and other application-specific parameters can significantly alter reclaim specifications. Please contact a Laidig technical sales representative regarding capabilities for specific applications.



At Laidig, YOUR success is OUR success.

WHAT WE OFFER:

- Custom Engineering and Design
- · In-House Manufacturing
- Construction Services and Support
- Multilingual Customer Service

If we design and install your storage and reclaim system, we guarantee it will work.

ADDITIONAL OPTIONS:

- Automatic Variable-Speed Drives
- Discharge Conveyor Systems
- Hydraulic Fluid Immersion Heater
- Ultra-Wear AR Design
- Stainless Steel Fabrication
- Hazardous-Environment Design







Laidig Systems, Inc.

14535 Dragoon Trail Mishawaka, IN 46544

574.256.0204 sales@laidig.com youtube.com/LaidigSystems