

LAIDIG PLANETAIRE SPECIFICATIONS

SPECIFICATIONS*	MODEL PL433 (HYDRAULIC)	MODEL PL443 (ELECTRIC)	MODEL PL833 (HYDRAULIC)
Storage Diameter	45′ (14m)	45′ (14m)	80′ (24m)
Auger Cutting Diameter	18" (45.7cm)	18" (45.7cm)	26" (66cm)
Auger Capacity	100 cfm (2.8m³/min)	100 cfm (2.8m³/min)	200 cfm (5.6m³/min)
Auger Rotation	50 RPM	50 RPM	35 RPM
Discharge Opening	9.33 ft² (0.86m²)	9.33 ft² (0.86m²)	9.33 ft² (0.86m²)
Reclaim Torque	lx (Base)	lx (Base)	4.2x
Reclaim Drive HP	-	100 HP	-
Hydraulic Power Unit	100 HP		200 HP

SMART CONTROLS

Our Smart Controls are critical components to your reclaim system, and can monitor your components and intelligently safeguard your equipment by providing alerts when potential issues arise.

Laidig Smart Controls include:

- Remote system monitoring
- · Remote maintenance assistance
- Preventative maintenance dialogue
 - Multi-language Laidig Machine Interface (LMI), loaded with custom Operation & Parts Manual



Several retrofit applications completed!





* Data shown conveys generalized specifications of the referenced Laidig reclaimers. Material characteristics and other application-specific parameters can significantly alter reclaim specifications. Please contact a Laidig technical sales representative regarding capabilities for specific applications.

DOMESTIC & INTERNATIONAL CUSTOMER SUPPORT

Laidig's dedicated, bilingual customer service teams are always on hand to assist. Whether you're looking for training (in-person or remote), spare parts, or help with international export logistics, we have you covered after the sale.

Our team can help you navigate any question or concern via telephone, or can schedule a trained Laidig field service technician to come directly to your jobsite to work alongside you.



Laidig Systems, Inc.

14535 Dragoon Trail Mishawaka, IN 46544

574.256.0204 sales@laidig.com

youtube.com/LaidigSystems

© Laidig Systems, Inc. 3/23